



Vario Shakers, Bühler

Small, reliable bench top shakers with special shaking motion.

Technical data:

Max. load: 2 kg (KL 2), 10 kg (TL 10/WS 10)
External dimensions (WxDxH): 355 x 455 x 195 mm, resp. 355 x 455 x 205 mm
Supply voltage: 230 V, 50/60 Hz (115 V on request)

| Article | Order No. |
|------------------------------------|--------------------|
| (1) Combination shaker KL 2 | 52 61 61150 |

"2 in 1" unit that can be switched over at any time from orbital to reciprocal motion.

Shaking area: 300 x 300 mm
Speed: 30 - 420/min infinitely variable
Shaking amplitude: 8 mm
Timer: 0 - 120 min or continuous operation

Basic unit includes:
Tray with 3 clamping rails and rubber mat

| Article | Order No. |
|---------------------------------|--------------------|
| (2) Rocking shaker WS 10 | 52 61 61140 |

Rocking shaker with slow, linear up-and-down motion.

Shaking area: 340 x 340 mm
Speed: 1 - 23/min infinitely variable
Rocking angle: 5° fixed
Timer: 0 - 120 min or continuous operation

Basic unit includes:
Rocking plate with rubber mat.
Multi-level rack with 2 additional trays available as an accessory.

| Article | Order No. |
|---|--------------------|
| Three-dimensional orbital shaker TL 10 | 52 61 61170 |

Same as WS 10, but with slow three-dimensional orbital motion.
Level inclination gyrating motion can be adjustable from 0° to 9°.



1



2